



Abdeckplatte/Cover



KLASSE
A
CLASS

Multimedia-Breitbandsteckdosen mit 5-65 MHz

- Separater Datenanschluss (F-Buchse) zum Direktanschluss eines Kabelmodems
- Breitbandige Ausführung der TV- und RF-Frequenzbereiche, gleiche Auskoppeldämpfungen am TV- und RF-Port
- Extrem hohe Entkopplung zwischen TV und Data-Port zur Vermeidung von Beeinträchtigungen der Fernseh-ZF durch einstrahlendes Rückwegsignal
- Galvanische Trennung der Innenleiter aller Anschlüsse zum Schutz gegen Brummspannungen und Ausgleichsströme
- Schirmungsmaß gemäß EN 50083-2 Klasse A:
>85 dB (5-300 MHz), > 80 dB (300-470 MHz),
>75 dB (470-862 MHz)
- **Abdeckplatte**, 80 x 80 mm, Farbe weiß RAL 9010, ist im Lieferumfang der Multimedia-Antennensteckdosen enthalten
- **Aufputzrahmen SAD 165**, 80 x 80 x 33 mm, Farbe weiß RAL 9010, für Multimedia-Antennensteckdosen

Multimedia broadband outlets with 5-65 MHz return

- *Extra Data port (F-female) for a separate connection of a cable modem*
- *TV- and RF-ports designed as broadband ports with equal insertion loss on TV and RF*
- *Very high isolation between TV and Data to avoid influences of TV-IF frequency by ingress of reverse signals*
- *Galvanic isolation protection against hum modulation and leakage currents (only inner conductors)*
- *Screening according EN 50083-2 class A:*
 - 85 dB (5-300 MHz), > 80 dB (300-470 MHz),
 - 75 dB (470-862 MHz)
- **Cover plate**, 80 x 80 mm, white coloured RAL 9010, will be delivered together with the multimedia outlets
- **Surface-mount frame SAD 165**, 80 x 80 x 33 mm, white coloured RAL 9010, for multimedia outlets

Allgemeine Produktübersicht / General Product Overview**Stichdose / End outlet**

Typ / Type	Anschluss / Port	Anschlussdämpfung im Frequenzbereich / Insertion loss in frequency range				Bestell-Nr. / Order-No.
		5 - 65 MHz	87,5 - 108 MHz	109 - 1.006 MHz	1.006 - 1.700 MHz	
btv 0665 DATA	IN-OUT					21900000
	TV	60 dB typ.	6,0 ± 1,0 dB	6,0 ± 1,0 dB		
	Radio	60 dB typ.	6,0 ± 1,0 dB	6,0 ± 1,0 dB		
	DATA	6,5 ± 1,0 dB	6,5 ± 1,0 dB	6,5 ± 1,0 dB		

Durchgangsdosen / Loop-through outlets

Typ / Type	Anschluss / Port	Anschlussdämpfung im Frequenzbereich / Insertion loss in frequency range				Bestell-Nr. / Order-No.
		5 - 65 MHz	87,5 - 108 MHz	109 - 1.006 MHz	1.006 - 1.700 MHz	
btv 1165 DATA-IM	IN-OUT	3,8 ± 0,8 dB	3,8 ± 0,8 dB	3,8 ± 0,8 dB		21910001
	TV	60,0 dB typ.	10,0 ± 1,0 dB	10,0 ± 1,0 dB		
	Radio	60,0 dB typ.	10,0 ± 1,0 dB	10,0 ± 1,0 dB		
	DATA	10,0 ± 1,0 dB	10,0 ± 1,0 dB	10,0 ± 1,0 dB		
btv 1265 DATA-IM	IN-OUT	2,5 ± 0,8 dB	2,5 ± 0,8 dB	2,5 ± 0,8 dB		21920001
	TV	60,0 dB typ.	12,0 ± 1,0 dB	12,0 ± 1,0 dB		
	Radio	60,0 dB typ.	12,0 ± 1,0 dB	12,0 ± 1,0 dB		
	DATA	12,0 ± 1,0 dB	12,0 ± 1,0 dB	12,0 ± 1,0 dB		
btv 1465 DATA	IN-OUT	1,8 ± 0,8 dB	1,8 ± 0,8 dB	1,8 ± 0,8 dB		21930000
	TV	60,0 dB typ.	14,0 ± 1,0 dB	14,0 ± 1,0 dB		
	Radio	60,0 dB typ.	14,0 ± 1,0 dB	14,0 ± 1,0 dB		
	DATA	14,0 ± 1,0 dB	14,0 ± 1,0 dB	14,0 ± 1,0 dB		
btv 1565 DATA	IN-OUT	2,0 ± 0,8 dB	2,0 ± 0,8 dB	2,0 ± 0,8 dB		21930015
	TV	60,0 dB typ.	15,5 ± 1,0 dB	15,5 ± 1,0 dB		
	Radio	60,0 dB typ.	15,5 ± 1,0 dB	15,5 ± 1,0 dB		
	DATA	15,5 ± 1,0 dB	15,5 ± 1,0 dB	15,5 ± 1,0 dB		
btv 1765 DATA	IN-OUT	1,5 ± 0,8 dB	1,5 ± 0,8 dB	1,5 ± 0,8 dB		21930017
	TV	60,0 dB typ.	17,0 ± 1,0 dB	17,0 ± 1,0 dB		
	Radio	60,0 dB typ.	17,0 ± 1,0 dB	17,0 ± 1,0 dB		
	DATA	17,0 ± 1,0 dB	17,0 ± 1,0 dB	17,0 ± 1,0 dB		
btv 1965 DATA	IN-OUT	1,0 ± 0,8 dB	1,0 ± 0,8 dB	1,0 ± 0,8 dB		21930019
	TV	60,0 dB typ.	19,0 ± 1,0 dB	19,0 ± 1,0 dB		
	Radio	60,0 dB typ.	19,0 ± 1,0 dB	19,0 ± 1,0 dB		
	DATA	19,0 ± 1,0 dB	19,0 ± 1,0 dB	19,0 ± 1,0 dB		