Building Access Terminal (BAT), Box, Neutral Cover, Gray, EMKA lock Size L, gray, EMKA lock, 16 cable strain reliefs



Part Number: BAT-LGE-ST001

The Building Access Terminal (BAT) Box is available in sizes XS (Small Floor Terminal), S, M, L, XL to address different capacity requirements. It is offered in white or grey color and lockable with a Screw- or EMKA-Lock.

Features and Benefits

Can be locked with lock or screw (M4)

Plastic FRNC

White or grey color

Cover completely removable

Clip to store documents

Side walls shaped to ensure maximum freedom of accessibility

Strain-relief for cables up to 12mm diameter

Modular configurable and extendable





Building Access Terminal (BAT), Box, Neutral Cover, Gray, EMKA lock Size L, gray, EMKA lock, 16 cable strain reliefs





Specifications

Design - Adapter	
Housing Color	Green

Design	
Fiber Count	12
Splice Tray Type	Own
Additional cable number reachable with accessories	16
Maximum cable number in basic unit with accessories	12
Number of Blank Modules	4
Cable entry type	Grommeted Slot
Number of Splice Trays	2
Pigtail Type	Individual with natural primary coating and yellow secondary coating
Housing Material	Plastic

Building Access Terminal (BAT), Box, Neutral Cover, Gray, EMKA lock Size L, gray, EMKA lock, 16 cable strain reliefs



General Specifications	
Fiber Category	Single-mode (OS2)
Access Type	Front access fixed
Lockable	Yes, front side
Mounting Type	Wall-Mountable
Application	Field Connectorization, Preterminated cables, splicing input

Optical Specification - Hardware	
Module Insertion Loss, Max	0.35 dB
Pigtail insertion loss	-65 dB

Shipping Dimensions	
Height	153 mm
Width	420 mm
Depth	340 mm

Connector Specs	
Connector Type	LC duplex

Environmental Conditions	
Temperature Range, Installation	-33 °C to 70 °C
Temperature Range, Operation	-33 °C to 70 °C
Temperature Range, Storage	-25 °C to 70 °C

Ordering Information	
Product Number	BAT-LGE-ST001
EAN Code	4042673811206

Building Access Terminal (BAT), Box, Neutral Cover, Gray, EMKA lock Size L, gray, EMKA lock, 16 cable strain reliefs



Ordering Information	
Weight	2.15 kg
Shipping Weight	2.4 kg
Units per Delivery	1/1



Corning Optical Communications GmbH & Co. KG • Lelpziger Strasse 121 • 10117 Berlin, Germany +00 800 2675 4641 • FAX: +49 30 5303 2335 • www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2022 Corning Optical Communications. All rights reserved.